


Early Design Choices: Capture, Model, Integrate, Analyze, Simulate

Jane T. Malin

(Team: L. Fleming, L. Flores, D. Throop, D. Lawler)

**Decision Based Design Structures Workshop
October 7, 2004**



Design: Incremental and Distributed

- Designs are constructed incrementally to meet requirements and solve problems
 - Requirements types: objectives, scenarios, constraints, ilities...
 - Problem/issue types: risk/safety, cost/difficulty, interaction, conflict...
- So, capture requirements, problems and solutions
 - Collect design and analysis products and make them accessible for integration and analysis
 - Link changes in design requirements, problems and solutions
 - Harvest design data for design models and choice structures
- System designs are constructed by multiple groups designing interacting subsystems
 - Diverse problems, choice criteria, analysis methods and point solutions
- So, support integration and global analysis of repercussions
 - System implications of point solutions
 - Broad analysis of interactions beyond totals of mass, cost...



- WorkIT** j.mallin / TESTGRP Home Status Report Action Report Help | Feedback | Admin | Personal Info | Logout

All Actions / [Search] Advanced Search

New 4.2 RDC All Workpapers / TESTGRP Home / RCC Literature (Open)

WORKSPACE HOME

Select Action Filter: ALL Open In Work Deferred Closed View Description

Actions Create Action

Due Date	Status	Priority	Title	ID	Assigned To
	Closed	Medium	CSCF references for Susan Ring	TESTORP1228A	Main, Jane

Files/Links/Notes Select: ALL - Analyses - Data - Mgt/Stats - Paperwork - Process/Exes - Graphics - Notes Add Note Add File/Link

Global Files/Links/Notes

Date Created	Category	Demo	Description	Title	Discipline	Created By
09/19/02			LINK	Gubins et al. progresses publications	TESTORP	main, jane
09/19/02			LINK	Link to Corbett 4 minutes for program design	TESTORP	main, jane
09/19/02			LINK	Link to report on system substructures for distributed processes and users	TESTORP	main, jane
09/19/02			LINK	Link to Stevens et al on Usage vs. Inspection Methods for Evaluating programs	TESTORP	main, jane

Internal Files/Links/Notes


Date Created	Category	Promote/Demote	Description	Title	Discipline	Created By
09/19/02			LINK	Link to Dix paper on interdependencies in coordinating teams	TESTORP	main, jane

Note Private Files/Links/Notes

Status Log Update Status Tasks Log Update Tasks


[09/19/02 by jmallin] : CSCF references for Susan Ring: TBD
[09/19/02 by jmallin] Also add Requirement Engineering references that relate to HCC methods. Due:






Harvest Design Data for Analysis


- Convert text – Reconciler parser/matcher
 - Requirements and constraints
 - Objectives, risks and mitigations
 - Procedure information and scenarios
- Match and map XML/RDF/OWL models
 - Map requirements to design representations
 - Phase/activity/operation, function, equipment, interaction/interface, constraint
 - Map problems to design structures
 - Map solutions to problem structures
- Collect metadata from process
 - New and changed conceptual design models that are elaborated to address design issues
 - Countermeasures, mitigations, solutions




Hazard Identification Tool Example

Convert requirements and risk text to derive early model






Analyze Repercussions Early



HIT Early Spacecraft Telecom Model
(Redundant Transmitters, Power, Thermal Control)




HIT Spacecraft Model Interaction Analysis

Mapped Model and Scenarios from HIT to CONFIG

Added **TCS** is another **noise** source. This noise can pass to vulnerable **Telesub transmitters** along **Power** distribution lines.

- Analyze interaction pairs and paths (HIT)
 - HIT: Hazard-vulnerability pairs and possible paths
- Simulate abstract operational scenarios (CONFIG)
 - Transmitter is abstract server with limited service rate (bandwidth) normalized to 1.0 capacity.
 - Science and engineering memory are clients with total load of 0.8.
 - When TCS is turned ON, noise travels from TCS to Xmitters via power connections and takes up 0.3 of capacity.
 - Xmitter 1 is overloaded (total 1.1 "requested"), changing transmitter data rate proportionally to $0.8/1.1 = 0.723$ (too slow).
 - Controller unsuccessfully tries to compensate by switching to backup Xmitter2, but transmission rate is unchanged.



CONFIG Abstract Spacecraft Model



Capture: Tame the Work Explosion

- Helpful Capture Tools
 - Primary goal is to get later long-term benefit when revisit or change the design
 - Reuse of design and analyses
 - Upgrades, repairs, accident analysis
 - Handling changing requirements, systems and environments
 - Provide short-term benefit to balance added short-term effort
 - Help capturing diverse types of design products
 - Help integrating information
 - Help search, access and get reports from diverse perspectives
 - Make metadata collection effortless
 - Help prioritizing decisions and areas for problem solving
 - Provide standard elements: Libraries and ontologies
 - Provide default requirements, problems, issues and solutions
 - Map and match diverse structures and representations
 - Accommodate and highlight special and new data
- In our story, the revised countermeasure for TCS noise has links to supporting analysis and simulation results⁷